



DISINFECTION SYSTEM

DISINFECTION SYSTEM

Catalogue 2012/13

SSC SERIES CHLORINATOR

Saltwater Solutions

Salt Chlorinators, are an alternative means of sanitizing your pool with chlorine using the process of electrolysis.

The electrolysis process is achieved by passing the salt water solution through an electrolytic cell which converts sodium chloride (salt) in the water into chlorine gas which, when dissolved in water become sodium hypochlorite (liquid chlorine).

Safe and respecting the environment, this technology brings you :

- Relaxation: Your pool is automatically disinfected
- Safety: Reduction in chlorine storage and handling
- Comfort: Clean, safe and crystal-clear water
- Health and well-being: Therapeutic, saltwater does not irritate eyes and dry out skin



Power Supply



Cell

Features:

3 models to choose: 15,25,45g/hr


Self cleaning reverse polarity

Quality titanium cells

Light transformer models


Maximum Working Pressure: 250kPa/36psi/2.5bar

Code 220V/50Hz	Model No.	Description			Salt Level (min)	Cell Output	Fiberglass Pool(Litres)	Concrete Pool(Litres)	Pool Light Voltage	Input Voltage /Freq.	IP Rating	Weight (kg)
88380601	SSC15-E	Standard Version	4000PPM		15gram/h	50,000	45,000	N/A	240V AC 50/60Hz	IPX4	6.5	
88380602	SSC25-E			25gram/h	75,000	70,000	7.4					
88380603	SSC50-E			45gram/h	120,000	110,000	9.7					
88380401	SSC15-T	With Time Clock		15gram/h	50,000	45,000	N/A	240V AC 50/60Hz	IPX4	6.6		
88380402	SSC25-T			25gram/h	75,000	70,000				7.5		
88380403	SSC50-T			45gram/h	120,000	110,000				9.8		
88380201	SSC15-TLT	With Time Clock			15gram/h	50,000	45,000	12V AC	240V AC 50/60Hz	IPX4	8.4	
88380202	SSC25-TLT	& pool light transformer		25gram/h	75,000	70,000	8.8					



SSC Salt Cell

The SSC's salt cell consists of a series of titanium electrodes with opposite charges. SSC's transparent salt cell housing allows visual inspection of the salt cell plates and enables monitoring of chlorine production.



Power Supply

- Power Supply enclosed in an UV & weatherproof enclosure
- Unit runs cool through design & innovation
- Displays are clear & easy to operate
- Time clock complete with Battery Backup

- ✓ Easy to read Digital Display
- ✓ Simple switch between manual and automatic operation
- ✓ Clear LED Operation
- ✓ Complete Output Control
- ✓ Full Diagnostic Display

SSC-TLT Chlorinator display shown

Options

Selecting a suitable unit

A number of factors will affect the selection of a salt water chlorinator.

- Size of pool
- Bather load
- Size & Turnover rate of filtration system
- Climate conditions
- See table below for general guide to choosing correct model



SSC-TLT Series

High Capacity Chemical Feeders

NEW

EMAUX high capacity feeders offer user-friendly solution for sanitizing large residential and commercial swimming pool using either chlorine or bromine tablets. They are heavy duty and able to provide automatic sanitization for pools up to 608000 litres. Both in-line and off-line plumbing installations are available in 2 sizes.

Features:

Treats pool/spa size(Unit: Litre, in a period of 24 hours)

MODEL: CL-01

10 ppm	25000L
5 ppm	50000L
2.5 ppm	100000L

MODEL: CL-02

10 ppm	27000L
5 ppm	54000L
2.5 ppm	108000L

MODEL: CLL-50

10 ppm	95000L
5 ppm	190000L
2.5 ppm	380000L

MODEL: CL-01A

10 ppm	45000L
5 ppm	90000L
2.5 ppm	180000L

MODEL: CL-02A

10 ppm	49000L
5 ppm	98000L
2.5 ppm	196000L


MODEL: CLL-75

10 ppm	152000L
5 ppm	304000L
2.5 ppm	608000L



TECHNICAL INFORMATION

Code	Model No	spec	Quantity	Total Weight	Valve Connections	A mm	B mm	C mm
88440207	CL-01	Ø30×16mm/pc Ø76×26mm/pc	102pc 11pc	2.0kg	1.5 inch 50mm	420	330	110
88440217	CL-02	Ø30×16mm/pc Ø76×26mm/pc	198pc 22pc	4.0kg	1.5 inch 50mm	705	330	110
88440208	CL-01A	Ø30×16mm/pc Ø76×26mm/pc	102pc 11pc	2.0kg	- 10mm	420	230	110
88440218	CL-02A	Ø30×16mm/pc Ø76×26mm/pc	198pc 22pc	4.0kg	- 10mm	705	230	110
88440302	CLL-50	Ø30×16mm/pc Ø76×26mm/pc	300pc 32pc	6.0kg	1.5 inch 50mm	580	600	225
88440303	CLL-75	Ø30×16mm/pc Ø76×26mm/pc	550pc 50pc	11.0kg	1.5 inch 50mm	760	600	225


1. MODEL: CL-01 \ CL-02 \ CLL-50 \ CLL-75 (IN-LINE)




2. MODEL: CL-01A \ CL-02A (OFF-LINE)



CL01-CL012



CL01A-CL01A



CLL50-CLSL75

